



HOSEBED CAPACITIES  
 ① - 1200' OF 5.00" LDH HOSE  
 ② - 600' OF 3.00" D.J. POLY HOSE

ALUMINUM BODY

SIDE ROLL AND FRONTAL IMPACT PROTECTION

**NOTE**  
 DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- BATTERY CHARGER LOCATED IN COMPARTMENT D3
- ONE ADJUSTABLE FULL WIDTH/FULL DEPTH SHELF IN COMPARTMENTS D1,D2,P1,P3,(2) IN D3
- ONE PAINTED ADJUSTABLE TILTING SLIDE-OUT TRAY IN COMPARTMENT P1,P2,P3
- ONE FLOOR MOUNTED SLIDE-OUT TRAY IN COMPARTMENT D1,P1,P3,R1
- ALL FOLDING STEPS TO BE TRIDENT WITH INTEGRATED L.E.D. LIGHT UNLESS SPECIFIED
- ONE HANNAY ELECTRIC REWIND CORD REEL MODEL 1618-17-18 LOCATED IN COMPARTMENT R1
- AIR INLET WITH KUSSMAUL AIR-EJECT ON D.S. PUMP PANEL

CHASSIS DATA	TITLE	1500-D-750P W/20G FOAM,189",FULL HEIGHT & DEPTH
MAKE	FOR	(2) X-LAYS,LIGHT TOWER,CABLE REEL
PIERCE		EUSTIS FIRE DEPARTMENT
MODEL		EUSTIS, FLORIDA
REV	DATE	BY
CH	IMPEL	

		JOB NO.	30107
		SCALE	DATE
DWG NO. 30107AD		DRAWN BY	JWO
		CHECKED BY	KBO
		SHEET SIZE	SHEET NO.
		D	1 OF 1